

Three-phase motors Cast iron housing

Type		SC2 225M6-695 AB
Design output	[kW]	30
Design torque	[Nm]	290
Class IE		IE2-91.7%
Efficiency determination		EN 60034-2-1
Duty type		S1
Design frequency	[Hz]	50
Design speed	[rpm]	985
Voltage	[V]	400/690
Connection		D / Y
Current	[A]	57.5 / 33.3
Relative pull-in current		6.2
Relative starting torque		1.9
Relative pull-out torque		2.9
Efficiency 100 / 75 / 50 %	[%]	91.7 / 91.6 / 91.1
Power factor		0.82
Th. cl.		155 (F/B)
Coolant temperature	[°C]	-20°C ... +40°C
Altitude above sea level	[m]	1000
Degree of protection IP		IP 55
Moment of inertia	[kgm ²]	0.52500
Motor weight	[kg]	294
Bearing D-side		6313 2RS/C3
Bearing N-side		6313 2RS/C3
Relubrication interval	[h]	-
Grease type		-
Grease amount	[g]	-
A-sound pressure level L _{WA}	[dB]	78.0
Options:		
Terminal box		Standard
Position of terminal box		On the top
Cable gland		Brass cable glands
Position of cable entry		Right
Shaft		Standard
Bearing		Easy bearing arrangement
Special information about the bearing		SKF bearing
Winding protection		1 set PTC resistors
Limit values to vibration velocity		Class A
Balancing		with half key
Colour		RAL 7030
Delivery conditions and/or official regulations		IEC / EN 60034-1

